bypass defense zones

Golden Security Technology Co.,Ltd

Add: Room 801, Huashenghui General Building, Jinhai Road, Xixiang St., Bao'an District, Shenzhen, Guangdong, China (Mainland)

Tel: +86-(0)755-66603665 Fax: +86-(0)755--25872283 Mobile: 8613128889471

E-mail: phoebe@cameralarms.com MSN:phoebe.security@hotmail.com skype:phoebe.security

Picture	Model Number:GS-G110E (900/1800,850/1900mhz)
Promotion	1.7 wired and 99 wireless defense zones;
	2,LCD screen with time clock display;
	3,Voice prompt for all operations;
	4,3 groups of timely arm and disarm;
	5,Can store 6 phone numbers: when alarming, system will make alarm call to these numbers automatically;
	6,Can store 3 SMS numbers: when alarming, system will send alarming SMS automatically;
	7,10-second automatic message recording;
	8,Built-in artificial intelligent digital voice announcer;
	9,Built-in artificial intelligent English message;
	10,Users can make calls by using keypad on alarm panel, just like a telephone;
Standard packing list	11,One-key-control function: Out Arm, Home Arm, Remote Arm;
One main unit	12,SOS, fire, gas, door, hall, window, balcony, and boundary places alarm;
One wireless door/window magnetic con	13,Real-time, delay, 24 hours,bypass defense zone, programming function;
One wireless PIR sensor	14,Wireless coding: easy to add additional wireless accessories;
Two remote controllers	15,Remote control Arm, Disarm, Monitor, and Intercom by phone;
One wired siren	16,Built-in AAA NI-HI rechargeable battery: make alarm when power off;
One AC adapter	17,Comply with CCC safety standard and GB12663-2001 national standard.
Technical Parameters	**Price (USD) Sample: FOB Shenzhen $65**
Wireless frequency:315MHZ,2262/4.7M	**10 to 50sets :$61**
	51 to 200sets:$58

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G130E GSM alarm system
	1. English menu SMS and voice reminder, 2.Can send SMS to switch the language **Chinese/English/Russian/Spanish** 3.Each zone has independent arm/disarm functions 4. 2 wired zones and 12 wireless zones 5.Can choose the siren on/off once you send the SOS alarm via panic button 6. With voice reminder when users operate the system 7.Works with external Microphone 8. Works with external speaker 9.Automatically send SMS to remind the user when the GSM signal becomes weak 10.Each wireless zone can use countless wireless sensors 11. Users can pre-record a voice message in the system and playback when system is alarmed 12.Send SMS text to 3 mobile phones and auto-dial 3 phones to inform the user 13.Users can use any phone to listen what is happening inside the building where the alarm is installed. 14.Program and control the system by keyboard, remotes, SMS or phone 15.Send SMS to inform users which zone is alarming and will call users when the system is triggered 16. Use SMS to change the zone name & content 17.Use SMS to inquiry the system status wherever 18.With password protection, System will inform users when an incorrect password is tried 3 times 19.Use any phone to call the system and anyone inside the house -can talk to you through a speaker. 20.Wireless Emergency function (24 hours zone) 21.With Backup rechargeable battery, system can work even if there is a power is failure.
Standard packing list	
One main unit	
One wireless door/window magnetic contact	
One wireless PIR sensor	
Two remote controllers	
One White siren	
One AC adapter	
One English user manual	
Technical Parameters	
1 Working power: AC=100~230V,	
2.Static current:<50mA (when not charging)	
3.Alarm current:<500mA	
4.Built-in Li-Ion backup battery: 3.7V	
1200mAH(rechargeable), Standby: around 16 hours,Full charging time: 12 hours	
	price :(USD) Sample :FOB Shenzhen $69 **10 to 50sets :$67** **51 to 200sets:$65**

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G160E (900/1800,850/1900mhz)
	1. Super GSM wireless signals, voice prompt, ease of use. Can install GSM phone card.
	2. Allow up to 6 wireless defense zones and 4 wired zones.
	3. Each can be defined as one of the 5 zone types including NORMAL, STAY, INTELLIGENT, EMERGENCY
	4. Two sets of scheduled arm/disarmed function, each time disarmed you can select the included period of time and different defense zone, eliminating of the manual procedure, realizing the beauty of automatic controls.
	5. Support configuration via phone (handset) or SMS messages to System Setup text messaging costs associated with the alarm panel.
	6. 6 groups voice alarm telephone number, 3 groups for SMS messaging. External communications without electricity information will be sen to 3 group messaging and dial 6 groups voice alarm phone number.
Packing list:	7. Support ISD automatic voice mailbox for playback message upon alert. Maximum length of voice message is 10seconds
One alarm host (main unit)	8. Telephone (phone) long-distance telephone control for arming, disarming, monitoring, remote announcement.
One Wireless door/window contact	9. 1 Set of normally open signal outputs, relay linkage output
One PIR sensor	10. Wireless intelligent study coding,Max 50 remote control and 50 sensors
Two remote controllers	11. Built-in Ni-Hi rechargeable battery and automatically switchable upon power failure
One siren(More than 110DB)	12. Panel integrated with newest either dual-band, triple-band, quad-band GSM/GPRS industrial graded module, stable and reliable.
One AC adapter	GSM frequency:
One English user manual	**GS-150E GSM900/1800MHZ**
	GS-150EA 850/1900MHZ
accessories:315MHZ/433MHZ	**Price (USD) Sample: FOB Shenzhen $55**
	10 to 50sets :$52

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G10E
	Descriptions: 1. Voice instructions for all the operation. 2. A single key to realize all related functions. 6. 10 zones, zone 1-6 are wireless zones, and zone 7-10 are wired zones. Each single zone setting is programmable. 5. 4 wired wired zones, 3. Up to 40pcs remotes supportable. 4. Up to105pcs wireless detectors supportable, which are allowed to be put into any 1-6 zone you like. 7. Any zone could be set to doorbell. "8. Any zone could be set to call or not, text or not and siren sound or not when alarming. " 9. Detector low voltage prompt and display. 10. 6 time points of auto arm and 6 time points of auto disarm. 11. One SMS could realize multi SMS instructions 12. Support Fetion by China Mobile. 13. Support IP dialing. 14. Watchdog function: panel alarm when the zone is not breached within predefined period (used to monitor the old or important place). 15. Intelligent zone: The panel alarms only when the zones are breached for pre-defined times. "16. 2 relay on/off output, which could be used as a switch to control home appliances (e.g. lamps, but its power voltage of home appliance by SMS). " 17. Built-in rechargeable battery, auto switch to battery power when main fails. 18. Support Control from a remote phone (landline or mobile).
Packing List:	
One alarm host (main unit)	
One Wireless door/window sensor	
One PIR sensor	
Two remote controllers	
One siren(More than 110DB)	
One wireless keyboard	
One AC adapter	GSM frequency:
One English user manual	**GS-10E GSM900/1800MHZ**
Specification of main unit:	**GS-10EA GSM850/1900MHZ**

Output power: DC12V	**Packaging Method**	**Packaging Dimension and Weight**
Input power: AC110V to 220V,50HZ or 60 H	**1 set of GS-G10E into one gift box**	**Gift Box:** G.W.:1.5kgs
Working hours of standby Battery(DC8.4V):	**5 gift boxes into one carton.**	Size:290(L)*270(W)* 85(H) mm
More than 10 hours		
Wireless frequency for above accessories:		**Carton:** G.W.:8.0kgs
315MHZ/433 MHZ		Size: 445(L)*305 x 290 (H)mm

	Price (USD) Sample: FOB Shenzhen $58
	5 to 50sets :$55
	51 to 100sets:$52

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G20E
	1.3 wired and 16 wireless defense zones 2.Can Auto-dial 5 phone No. and send SMS to 7 phone No. while alarming. 3.normally open/closed signal output 4.10-second voice message recording function 5.Can call the mainframe any time and listen what happened in the alarm area. 6.Can arm/disarm and program the system by wireless keyboard, SMS or phone 7.Call in to set alarm ON, OFF, Monitor, Output, Intercom
Packing list Includes	8.can connect wired & wireless PIR sensor, door/window contact, smoke detector, gas leakage detector, glass break sensor etc. Each wireless zone can match numberless wireless sensors.
One alarm host (main unit)	9.With voice reminder & password protection while the system is working.
One alarm host (main unit)	10.Can connect with intercom. You can talk to the mainframe with intercom.
One Wireless door/window magnetic contac	11.Switch to Backup rechargeable battery when the power is failure or cut by intruder and will send SMS and call you.If the power is recoverd, it will also send sms to you.
One PIR sensor	12.Wireless signal transmission, with Human voice guide and easy to use, and don't fear for cutting wire by the intruders.
Two remote controllers	13.With learning code programme method,it's easy to operate
One siren(More than 110DB)	14.2 output port can be used to three lights or other home appliances.1 relay output can be connect with DVR
One AC adapter	**Price (USD) Sample: FOB Shenzhen $52**
One English user manual	**5 to 50sets :$50**
	51 to 100sets:$48
	101 sets to 200 sets:45

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G30E
	Description and Main functions
	1.Wavecome GSM module.
	2.8 wireless zones(1 wireless SOS zone, 1 wireless fire alarm zone, and the other 6 wireless zones can be definded by user).
	3.You can connect wireless emergency button, wireless PIR sensor, wireless door/window contact, wireless smoke detector, wireless gas leakage detector, wireless glass break sensor etc. Each wireless zone can match numberless wireless sensors.
	4.Can Auto-dial 3 phone No. and send 3 SMS while alarming.
	5. Arm/disarm by remote controller and SMS.
	6.It's easy to operate.
Includes	7.With voice reminder & password protection while the system is working.
Packing list:	8. Can connect with intercom. You can talk to the mainframe with intercom.
One Wireless door/window magnetic contact	9. Switch to Backup rechargeable battery when power is failure or cut by intruder.
One Wireless door/window magnetic contact	10.Wireless signal transmission, and don't fear for cutting line by the intruders.
One PIR sensor	14. Wireless Emergency function:you can press the button to alarm immediately in order to get help if in emergencies.
Two remote controllers	15. Can send alarm signals to monitoring center through GSM network, such as the police station.
One siren(More than 110DB) One wireless keyboard	GSM frequency:
One AC adapter One English user manual	**GS-30E GSM900/1800MHZ**
	GS-30EA GSM850/1900MHZ

Specification of main unit:	**Packaging Method**	**Packaging Dimension and Weight**	
Output power: DC12V	**1 set of GS-G30E into one gift box**	**Gift Box:**	G.W.:1.5kgs
Input power: AC110V to 220V,50Hz or 60 Hz	**5 gift boxes into one carton.**		Size:290(L)*270(W)* 85(H) mm
Working hours of standby Battery(DC8.4V):			
More than 15 hours		**Carton:**	G.W.:8.0kgs
Wireless frequency for above			Size: 445(L)*305 x 290 (H)mm

accessories:315MHZ/433MHZ	**Price (USD) Sample: FOB Shenzhen $58**
	10 to 50sets :$56
	51 to 200sets:$54
	101 sets to 200 sets:48

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G40E
	Description and Main functions
	1.Wavecome GSM module.
	2.8 Wireless zones (1 wireless SOS zone, 1 wireless fire alarm zone, the other 6 wireless zones can be defined by user), 1 external power failure alarm zone and 2 wired zones.
	3.You can connect wired & wireless PIR sensor, door/window contact, smoke detector, gas leakage detector, glass break sensor etc. Each wireless zone can match numberless wireless sensors.
	4.You can record your voice in the mainframe in advance and will call you or the police and play the voice while alarming.
	5.Can send SMS to 3 mobile phone No. and Auto-dial 3 phone No. while alarming.
	6.You can call the mainframe any time and listen what happened in the alarm area.
	7.You can arm/disarm and program the system by wireless keyboard, SMS or phone
	8. Report the alarm zone & type by SMS or voice and can be remote controlled by SMS and telephone.
Packing List:	9. Modify name of wireless zones and check the status of alarm mainframe by SMS.
One alarm host (main unit)	10.With voice reminder & password protection while the system is working.
One Wireless door/window sensor	11. Can connect with intercom. You can talk to the mainframe with intercom.
One PIR sensor	12. Switch to Backup rechargeable battery when the power is failure or cut by intruder and will send SMS and call you.If the power is recoverd, it will also send sms to you.
Two remote controllers	13.Wireless signal transmission, with Human voice guide and easy to use, and don't fear for cutting wire by the intruders.
One siren(More than 110DB)	14. Wireless Emergency function(24 hours zone):you can press the button to alarm immediately in order to get help if in emergencies.
One wireless keyboard	15.Can send alarm signals to monitoring center through GSM network, such as the police station
One AC adapter	**GSM frequency:**
One English user manual	**GS-G40E GSM900/1800MHZ** **GS-G40EA GSM850/1900MHZ**

Specification of main unit:	**Packaging Method**	**Packaging Dimension and Weight**	
Output power: DC12V	**1 set of GS-40 into one gift box**	**Gift Box:**	G.W.1.5kgs
Input power: AC110V to 220V,50HZ or 60 H	**5 gift boxes into one carton.**		Size:290(L)*270(W)*85(H)mm
Working hours of standby Battery(DC8.4V):		**Carton:**	G.W.8.0kgs
More than 10 hours			Size: 445(L)*305(W)*290 (H)mm
Wireless frequency for above accessories:	**GS-G40E**		
315MHZ/433 MHZ	**Price: Sample(USD): FOB Shenzhen $78**		
	10 to 50sets :$76		
	51 to 200sets:$74		

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G50E
	The alarm system is based on GSM network. With a GSM SIM card, it can be used wherever you want and no need to connect any wire, which is convenient and easy to install and use.
	Main functions,
	1.English language SMS and voice reminder, Spanish/Chinese/Russian for optional
	2.With Independent arm function,which can only disarm by SMS
	3.With 2 wired zones, 12 wireless zones
	4.With 3 Relay output to control your home appliances
	5.With voice reminder when users operate the system
	6.Work with external Microphone
	7.Work with external speaker
Packing List:	8.Auto send SMS to remind users when GSM signal becomes weak
one Main unit	9.Work with wired & wireless PIR, door/window sensor, smoke/gas detector, glass break sensor etc.
one Magnetic Door Sensor	10.Each wireless zone can match countless wireless sensors.
Two Wireless Remote Controls	11.Users pre-record voice in the system and play the voice when system gives alarm
one Wireless Programming Keypad	12.Send SMS to 3 mobile phones and auto-dial 3 phones to inform the users
one PIR Motion Sensor	13.Users use any phone to listen what is happening inside the house whenever & wherever.
one Mini Siren	14.Program and control the system by keyboard, remotes, SMS or phone remotely.
one 12vDC Power Supply	15.Send SMS to inform users which zone is alarming and will call users or the police after system is triggered
Specification:	16.Use SMS to change the zone name & content
a) GSM network frequency Standard:	17.Use SMS to inquiry the system status wherever
900/1800MHZ, 850/1900MHZ optional	18.With password protection, System will inform users when input wrong password for 3 times
b) External power failure alarm:	19.Use any phone to call the system and anyone inside the house -can talk to you through a speaker.
Start-time: less than 1s	20.Wireless Emergency function (24 hours zone)
c) Alarm response time	21.With Backup rechargeable battery, system can work even when the power is failure or cut by intruder.
Less than 10s (GSM in normality)	22.Send SMS to inform you when the power is failure or returns to normal.
d) Power requirements:	23.Support monitoring center through GSM network to the police station or management centre
AC 220V 50Hz	
Standby lithium battery:	**GS-G50E**
DC8.4V, 700/800mA, 4000mA optional	**Price: Sample(USD): FOB Shenzhen $88**
Standby battery working hours:	**10 to 50sets :$85**
more than 10 hours, 4000mA for over 3 days	**51 to 200sets:$82**

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Piceture	Model Number:GS-G180E (900/1800,850/1900Mhz)
	1.Touch keypad; Big LCD displays; Internal antenna
	2.GSM+PSTN dual network. If PSTN is disable,it will switch to GSM automatically
	3.Calendar+5 alarm call/SMS No.+1 alarm CID call No.+1 upload SMS No.+ 10S record+ Arm Delay + Alarm Delay + Alarm Beep Setting+ Call-in time setting+ Wireless Program+ Zone Attribute Setting+ User password + Program Password + Reset + Alarm History + Status History
	4.30 wireless zones + 8 wired zones, every zone attribute, name, bypass, alarm delay, intelligent door sensor function, beep indication could do free setting.
	5.Alarm Inform Mode: PSTN Call, GSM Call, GSM SMS
Standard packing list	6.Alarm SMS include alarm zone and sensors name
One alarm host	7.Work with Ademco Contact ID protocol(alarm information, status information, AC power off and recover, Low voltage,
One wireless door/window magnetic contact	8.Support wireless “ding-dong” doorbell function
One PIR motion sensor	9.Alarm priority, Reset, activate and disable alarm call and alarm SMS
Two remote controllers	**Advantages: 1.touch keypad 2. internal antenna and nice look. 3.Many language menu available**
One AC adapter	**4.bigger LCD 5. ABS fire-proof material 6. GSM+PSTN dual-network**
One English user manual	**GSM frequency:900/1800/850/1900mhz**
	Price(USD)Sample:FOB ShenZhen$95
	10 to 50sets:$92
	51 to 200 sets:$89

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G80AE (900/1800,850/1900mhz)
	1. Touch Screen
	2. LCD Screen displays Date, Day of the week, Time, and current Armed Status
	3. Supported Languages: Simple Chinese\ Traditional Chinese\ English\ German\ French\ Russian\Danish and more.
	4. 29 wireless zones (Each zone supports up to 4 sensors) and 2 dedicated zones for remotes (Supports up to 4 remotes or wireless keypads per zone)
	5. 8 more wired zones(Optional), add US $2.5 cost
	6. Intelligent logic analysis technology, corresponding zone and sensor name can be displayed.
	7. Support seperated wireless doorbell, and will sound chord “Ding-Dong” from alarm hot panel when you press doorbell button.
	8. Can dial up to 5 phone numbers in sequence
	9. Record up to a 10 second greeting for the auto-dialer, Then play the greeting back.
	10. Arm\ Disarm the system by: SMS, Main Host(Keypad), Wireless Keypad, Keychain Remotes, or even remotely by phones. (PSTN alarm don’t support SMS)
	11. Available in both AC\DC with Low-voltage Indicators
Standard packing list	12. Learning sensors to alarm host, very easy operation.
One main unit	13. Store up to 100 alarm records(alarm history) and 100 arm\disarm records(arm/disarm operation history)
One wireless door/window magnetic con	14. Support CID uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function
One wireless PIR sensor	15. Non-volatile chip, information stored automatically when off power
Two remote controllers	16. Check door\window status automatically (This is when the system is disarmed only, if a door is opened, it will sound fast “bi bi bi”)
One strobe siren	17. AC FAILURE NOTIFICATION to CID Center monitoring station（Optional function）
One AC adapter	18. Support wireless “ding-dong” doorbell function (Optional)
One English user manual	**GSM frequency:**
Technical Parameters	**GS-G80AE GSM900/1800MHZ**
1 Working power: AC=100~230V,	**GS-G80AEA GSM850/1900MHZ**
2.Static current:<50mA (when not chargi	**Price (USD) Sample: FOB Shenzhen $93**
3.Alarm current:<500mA	**10 to 50sets : $90**
4.Built-in Li-Ion backup battery: 3.7V	**51 to 200 sets : $88**
1200mAH(rechargeable), Standby: around 16 hours,Full charging time: 12 hours	**Note:GS-G80AE has 868mhz version**

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G80CE (900/1800,850/1900mhz)
	1.Touch keypad, blue backlights; blue LCD displays Date, Day of the week, Time and current Armed Status;
	2. Concise icons guided LCD display. Suitable for every market all over the world.
	3. 2 /4 Band GSM net-work. Supports phone call alarm and SMS alarm at the same time, SMS includes zone number and alarm event type. Automatically switch to GSM dialing when telephone line is cut.
	4. 15 wireless zones (Each zone supports up to 4 sensors) and 1 dedicated zones for remotes (Supports up to 10 remotes or wireless keypads per zone). Supports 2 wired zones (optional).
	5.Can preset up to 6 phone numbers and dial in sequence. Every mobile phone number can be set for phone call alarm or SMS alarm.
	6. Intelligent logic analysis technology, corresponding zone number can be displayed on LCD screen.
	7.Record up to a 10 second greeting for phone call alarms which can be heard when answering the alarm call.
	8.Arm\ Disarm the system by 5 ways: SMS, Main Host (Keypad), Wireless Keypad (optional), Keychain Remotes, and phone calls. (PSTN alarm don't support SMS)
	9.Available in AC\DC, Low-voltage alerts.
	10. "One-Key" arm？ , studies sensors to alarm host, very easy operation.
	11. Non-volatile chip, information stored automatically when off power.
	12.Door\window status self-check and "Ding Dong" doorbell can be completed as optional functions.
Standard packing list	13.8 zone electrical appliance control and 8 groups of scene control can be completed as optional functions.？
One main unit	14.Support CID uploading to CMS (Center monitoring Station) .can user our GSM SMS CID connector to complete this function.
One wireless door/window magnetic sensor	15.Disconnection alarm, auto priority to occupy the telephone and monitoring function to hear what is happening.
One wireless PIR sensor Two remote controllers	16. Built-in Lithium backup battery, perfect system self-check, alerts of landline phone cable cut, no SIM card, alarm host low power,no external power supply and even low battery power of sensors.
One wireless strobe siren	

One AC adapter	**Packaging Method**	**Packaging Dimension and Weight**	
Specification of main unit:	**1 set of GS-G80CE into one gift box**	**Gift Box:**	G.W.:1.2kgs
1 Working power: AC=100~230V,	**5 gift boxes into one carton.**		Size:290(L)*270(W)* 85(H) mm
2.Alarm current:<500mA		**Carton:**	G.W.:6.7kgs
3.Built-in Li-Ion backup battery: 3.7V			Size: 445(L)*305 x 290 (H)mm
4.1200mAH(rechargeable), Standby:	**Price (USD) Sample: FOB Shenzhen $85**		
16 hours,Full charging time:12 hours	**10 to 50sets : $82**		
	51 to 200 sets : $78		
	Note:GS-G80CE has 868mhz version		

Picture	Model Number:GS-G80DE (900/1800,850/1900mhz)
	Remark:
	The features of GS-G80DE is the same as GS-G80CE,only appearance is different.
	Price (USD) Sample: FOB Shenzhen $85
	10 to 50sets : $82 51 to 200 sets : $78
	Note:GS-G80DE has 868mhz version

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G70E (900/1800,850/1900mhz)
	1. Color LCD screen, keypad with blue light
	2 ..Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function
	3. Maximum 30 wireless zones,support 8 more wired zones, add US $2.5 cost .
	4. LCD display with calender, available in English/Chinese/Germany/Russian/French and Japanese etc. Non-volatile chip, information stored automatically when power off.
	5. One-key arm operation,With learning code programme method,it's easy to operate
	6.Preset 5 Telephone & 5 SMS number to inform alarm
	7. Switch to Backup rechargeable battery when the power is failure or cut by intruder.
Standard packing list	8. 5 methods Arm/Disarm: Remote Controller, Host Keypad, Remote Keypad(options),Telephone/Mobile phone and GSM SMS
One main unit	9. Internal & external antenna for your options
One wireless door/window magnetic contact	10. It will use GSM and has capability for land line where GSM is not possible
One wireless PIR sensor	11. External power failure and external power return informed via SMS
Two remote controllers	12. 2^{20} wireless address encode reduce the rate of same code greatly.
One Wireless strobe siren	13. Learning code wireless accessories.
One AC adapter	14. SMS control & program
One English user manual	15. SMS modifies wireless zones name.
	20. Entry delay alarm.
Specification of main unit:	22. Internal MIC or external high sensitivity MIC (optional)
Output power: DC12V	25. Working with monitoring center, such as police station
Input power: AC110V to 220V,50Hz or 60 Hz	**GSM frequency:**
Working hours of standby Battery(DC8.4V):	**GS-G70E GSM900/1800MHZ**
More than 15 hours	**GS-G70EA GSM850/1900MHZ**
Wireless frequency for above accessories:	**Price (USD) Sample: FOB Shenzhen $92**
315MHZ/433MHZ	**10 to 50sets : $88**
	51 to 200 sets : $86
	Note:GS-G70E has 868mhz version

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Dual-net GSM+PSTN alarm

Picture	Model Number:GS-G80BE (900/1800,850/1900mhz)
	Remark:
	The difference between GS-G80AE and GS-80BE
	GS-G80AE is GSM alarm system GS-80BE is Dual-net GSM+PSTN alarm
	All the functions and specification are same except for above
	Price (USD) Sample: FOB Shenzhen $98
	10 to 50sets : $95
	51 to 200 sets : $92
	Note:GS-G80DE has 868mhz version

Picture	Model Number:GS-G90E (900/1800,850/1900mhz)
	1.LCD and blue back-up light, English voice prompt for every step
	2.85 events record history about arming, disarming, and alarming.
	3.Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station) .
	4.The user can listen in, speak, sound siren, disarm remotely from users phone,when there is alarm
	5.groups timed auto arm/disarm, Away/Stay arm optional
	6. Every zone can be programmed seperately, it can set to be: watchdog zone, exit/entry delay, 24 hours zone, sounder/silent
	7.Every detector can be set to doorbell when disarmed, every detector can be set to locally alarm((do not dial out) when triggered in disarmed mode
	8.Siren can be set to be on/off.
One package includes:	9.Each zone can be seperately armed/disarmed (24 hours zone can not seperately disarmed)
One main unit	10.Unique watchdog function, monitor the old, patient or important place. When one zone is set to be watchdog zone, during a programmed time, if the sensor not triggered, then the panel would alarm
One wireless door/window magnetic contact	
One wireless PIR sensor	11.Built in rechargable battery which backs up 12 hour when main fails; Built-in siren, and timer Ic, the time keeps right after power off.
Two remote controllers	12.Remote control, listen in, speak, arm, disarm, or turn on/off the siren from a remote phone.
One AC adapter	Zone is defaulted as below: 1: fire, zone 2: panic zone 3: entry/exit delay, zone 4.5.6: burglar, zone
One English User manual	7: stay arm zone (interior zone) zone 8: medical
	Price (USD) Sample: FOB Shenzhen $84
	20 to 50sets : $80
	51 to 200 sets : $77

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-G100E (900/1800,850/1900mhz)
	1. Full compliance with ADEMCO CONTACT ID
	2. 8 wireless zones and 2 wired zones, exclusive zone 0 for key fob, each zone programmable
	3. Zone type inquiring and programming at random (Zone type: watchdog zone, exit/entry delay, 24 hours zone, sounder/silent when alarming, armed/part armed zone, sensor/no sensor in the zone)
	4. Three attributes are programmable for each detector, one attribute is programmable for each Key Fob
	1).Detector 1 In the disarmed mode: sounder when alarming once triggered;
	In the armed mode: dial the C.S. number or users number.
	2). Doorbell function: Detector will be Door Bell when disarmed
	3). Low voltage display: Panel can receive the detector low voltage signal and display zone number and detector NO. on theLCD and sound a beep
One package includes:	5. The Key Fob and detector logging in, without the need for coding (user can add and reduce detectors freely), learning code
One main unit	6. Multimode arming methods: Away arming, Part arming, 24 hour arming, and every zone could be separately armed/disarmed
One wireless door/window magnetic contact	7. 85 event log about arming, disarming, and alarming (with time and date stamp), viewable directly on the panel LCD
One wireless PIR sensor	9.When alarming, the C.S operator or the user could listen in, speak, or start the siren from a remote place
Two remote controllers	10. 6 time points of timed Auto-Arming, 6 time points of timed Auto-disarming (24 hour mode)
One AC adapter	12. Panel can receive the detector low voltage signal and display zone number and detector number on the LCD and sound a beep
One English user manual	13 Line sensing and Alarm priority: panel automatically check the line and alarm even when it is engaged or cut.
	1).Each detector could be set to Door Bell, when it is triggered, the panel sound a ding-dong
Specifications	2).Control from a remote phone: Remotely arming/disarming, listen in, speak to the occupants
1 Working power: AC=100~230V, DC=12V 1A	3).Entry/Exit delay, voice prompt both when arming and being triggered
2.Static current:<50mA	4).External power failure alarm,when the power was cut ,the alarm host will send SMS to inform user.
3.Alarm current:<500mA	5).SOS alarm feature,alarm host can work with emergency button
4.Built-in Li-Ion backup battery: 3.7V	6).Built-in high capacity rechargeable backup battery, auto recharge
1200mAH(rechargeable), Standby: around 16 hours,	7).Wireless signal transmitting test
Full charging time: 12 hours	8).Engineer Option. Listen to the dial tone of DTMF
	Price (USD) Sample: FOB Shenzhen $82
	20 to 50sets : $78
	51 to 200 sets : $75

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

PSTN Alarm

Picture	Model Number:GS-T08E
	1,100 wireless and 8 wire defense zones.
	2,Blue backlighting graphic display.
	3,6 groups of voice alarm phones (mobile phone), and 2 groups of phones in alarm receipt center.
	4,Built-in perpetual calendar and clock; auto record alarm history by time sequence.
	5,Message recording playback: human recording, synchronous playback for recording effect in audition.
	6,More defense modes: remote defense, keypad defense, and non-local remote defense by telephone; stay-in defense, timing defense, and individual defense i
	7,Programming of defense zone type: all zones could be programmed via keypad for immediate, delayed, 24-hour and bypass alarm modes.
	8,Alarm Position Programming: Intelligent automatic speech recognition: SOS alarm, fire alarm, gas leak, magnetic contact alarm, hall alarm, window alarm, balcony alarm, and perimeter alarm
	9,Timing arm and disarm: console features automatic timing arm and disarm.
	10,Two arm models:
Technical parameters:	1)home alarm model:console music and voice alarm, external siren mute
a)Input Voltage: DC12V 500mA	2) home away arm model:console voice alarm, loud external siren alarm.
b)Standby Current: 50mA	11,Password Recovery: Whether the console is in defense or withdrawal, the lost password can be recovered.
c)Alarm Current: 450mA max	12,Intelligent learning code: intelligent learning code, newly added with detector which is prompt and efficient, and convenient and simple.
e)Output current: DC12V 150mA	13,Event Log Query: console automatically records 45 pieces of all information concerning defense, withdrawal and alarm events.
f)Wireless Frequency: 315MHz	14,Line priority alarm: the console will cut the busy call and switch to priority alarm in case of the alarm during ongoing call, no matter incoming or outgoing call.
g)Coding Method: 2262 IC / 4.7MΩ	15,Phone disconnection detection: automatic detection and alarm warning in line disconnection, for anti-sabotage of telephone lines.
h)Alarm noise: 110dB	16,Remote control: through remote phone (cell phone) dial-up, many operations could be realized, like defense, withdrawal and on-site monitoring by the console in the remote control form.
i)Back-up Battery: AAA 7.2V	17Console is equipped with battery box, with optional AAA NI-HM rechargeable battery.Console meets 3C safety standards and national standard GB12663-200
j)Environment Temperature: -20℃ ～ +55℃	18,Compatible with internationally accepted protocol of alarm receipt center: Ademco Contact ID alarm communication protocol.
	Price (USD) Sample: FOB Shenzhen $38
	10 to 50sets :$36
	51 to 200 sets : $34

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-T01A
	1. LED display, 15 wireless zones, can work with up to 60 wireless sensors (each zone supports up to 4 sensors)
	2.You can connect wired & wireless PIR sensor, door/window contact, smoke detector, gas leakage detector, glass break sensor, emergency button etc. Each wireless zone can match numberless wireless sensors.
	3. With 13 working LEDs and control keyboard on the mainframe.
	4.You can record your voice in the mainframe in advance and will call you or the police and play the voice while alarming.
	5.Can Auto-dial 6 phone No. while alarming.
	6.You can call the mainframe at any time and listen what happened in the alarm area,
	and you can arm/disarm and program the system by control keyboard on the mainframe & phone
	7..Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function
	8.With voice reminder & password protection while the system is working.
	9. Remote monitor and check the alarm zones by phone.
	10. Arm mode: immediate arm, delayed arm and partial arm.
	11. Can set the ring times of alarm mainframe. When there is coming call, the mainframe can get through it automatically after checking the preset ring times.
One package includes:	12. Can choose to set/cancel the alarm function of cutting telephone line.
One main unit	13. Switch to Backup rechargeable battery automatically when power is failure or cut by intruder.
One wireless door/window magnetic contact	11. When the system alarms, it can report and follow up the latest alarm zones.
One wireless PIR sensor	14. Can send alarm signals to monitoring center through telephone network, such as the police station.
Two remote controllers	
One strobe siren	**Price (USD) Sample: FOB Shenzhen $45**
One AC adapter	**10 to 50sets :$42**
One English user manual	**51 to 200 sets : $39**
	Note:GS-T01A has 868mhz version
Picture	**Model Number:GS-T01B**
	Remark:
	The difference between GS-T01A and GS-T01B: GS-T01B has following extra features:
	1) LCD display
	2) With year/week /time/armed status
	3) Available to display in the following languages: English, Chinese, German, Russian, French, Japanese etc.
	4) 30 wireless zones, can work with up to 120 wireless sensors (each zone supports up to 4 sensors)
	5)Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function
	All the functions and specification are same except for above
	Price (USD) Sample: FOB Shenzhen $60
	10 to 50sets :$58
	51 to 200 sets : $55
	Note:GS-T01B has 868mhz version

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

GPRS MMS Alarm System

Picture	Model Number:GS-M22E (900/1800,850/1900mhz)
	***With camera & PIR itself**
	***Can send MMS to your mobile phone.**
	***Can Send picture to your E-mail.**
	***Can match wireless detectors/sensors with alarm host by learning code.**
	***Build-in 2G SD card to store pictures(In standard package,there is no SD card)**
	1. Built-in 300,000 pixels night vision digital camera,suitable fo night use.
	2. Support 2G SD card , convenient for long-term storage of image evidence.
	3. Support PIR motion detecting with photo-taking.
	4. Support SMS, MMS,phone,E-mail to alarm.
	5. Image size is adjustable: QCIF(160×128)、CIF(320×240)、VGA(640×480)
	6. Can pre-set arm / disarm time,convenient for user or alarm center to control.
	7. The time of reporting can be set regularly .
Technical parameter	8. 16 wireless zones,each can be prgrammed independently,eg : arm,disarm and 24-hour arm.
Static Current： 40 mA	9. Can set 5 user phone numbers ,can listen-in when alarming.
Power Supply： 9-12 V	10.Can set 2 email address: send scene image alarm info to E-mial.
Support PHASE2/2 & protocol	11.Support GSM / CDMA mobile phone to receive SMS alarm and send SMS commands to control the system.
Receive Coding： ASK	12.Can send scene color images to mibile phone immediately after alarming .
Receive Frequency： 315/433 MHz	14.User can remotely listen-in by calling the host.Can hear the voice at the scene .
Remote Control Distance :30m	13.Can capture scene color photos and send to user by sending SMS command.
Detectors： 16	14.Built-in Li battery, AC-DC shift, automatically recharge
	15.Password operation ensure the security of system.
	16.Support Real-Time Clock adjustment, SD card image stored with time, convenient for inquire.
	17.Wireless system, no need to set wire and easy to install. Special suitable for garage, storeroom, and other places where there is no wired network.
	Price (USD) Sample: FOB Shenzhen $90
	10 to 50sets :$87
	51 to 200 sets : $82

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

3G Video ALARM SYSTEM

Picture	Model Number:GS-98A 850/900/1900/2100MHZ
	1. Camera can send alarm messages by SMS, video call, voice call
	2.Max 15 wireless alarm sensors can be added.
	3.Support to record the alarming image to the camera
	4.Wireless remote control: it can arm ,disarm or send emergency alarm
	5.Up to 11 telephone numbers can be pre-stored in the system
	6.Including the intensity detection and infrared lighting functions
	7. Motion detection function within 6m
	8.using high sensitivity MIC, can make calls within 7m.
Standard Paking:	9.you can call the video phone to check the video of monitoring
one alarm host	10.3G standard:WCDMA,Built-in 2GB TF card
one wireless door sensor	**Price (USD) Sample: FOB Shenzhen $119**
	5 to 50sets :$117
	51 to 100sets:$115
	101 sets to 200 sets:112
Picture	**Model Number:GS-98B 850/900/1900/2100MHZ**
	1. Camera can send alarm messages by SMS, video call, voice call
	2.Max 15 wireless alarm sensors can be added.
	3.Support to record the alarming image to the camera
	4.Wireless remote control: it can arm ,disarm or send emergency alarm
	5.Up to 11 telephone numbers can be pre-stored in the system
	6.Including the intensity detection and infrared lighting functions
	7. Built-in PIR detection function within 6m
	8.using high sensitivity MIC, can make calls within 7m.
Standard Paking:	9.you can call the video phone to check the video of monitoring
one alarm host	10.3G standard:WCDMA,The outer TF card
one wireless door sensor	**Price (USD) Sample: FOB Shenzhen $112**
two remote controller	**5 to 50sets :$108**
	51 to 100sets:$105
	101 sets to 200 sets:103

Quotation

Home Security alarm system (Mainly used in House,office,Factory,etc.)

Picture	Model Number:GS-6828 850/900/1900/2100MHZ
	1. Camera can send alarm messages by SMS, video call, voice call
	2.Max 15 wireless alarm sensors can be added.
	3.Support to record the alarming image to the camera
	4.Wireless remote control: it can arm ,disarm or send emergency alarm
	5.Up to 11 telephone numbers can be pre-stored in the system
	6.Including the intensity detection and infrared lighting functions
	7. Built-in PIR detection function within 6m
	8.Built-in MIC and speaker,enables two-way intercom and on-site shouting function
Standard Paking:	9.you can call the video phone to check the video of monitoring
one alarm host	10.3G standard:WCDMA
one wireless door sensor	11.The outer TF card
two remote controller	12.3G frequency:850/900/1900/2100MHZ
	Price (USD) Sample: FOB Shenzhen $129
	5 to 50sets :$125
	51 to 100sets:$122
	101 sets to 200 sets:119